

OPERATING INSTRUCTIONS

The default operation mode of the ALLGIG-HS REN is to allow "Video in motion" and navigation entry while the vehicle is in motion and A/V Input. These features, can be added to or removed with a PC via our USB interface and software, available for download at;

www.nav.tv

You will now be able to view TV/DVD in motion as well as enter navigation destinations on the move. And add an A/V input.

The Switchable extras are;

*A/V output,

*Reverse Camera input.

Note;

The Video Out on the AV harness will only display the image from the built-in DVD player. The camera and A/V inputs will not display through the Video Out, and the internal DVD will pause when A/V is selected.

If the vehicle did not have a backup camera option, it will now be enabled from the MENU --> System Setup --> Camera Setup screen.



NAV TV (Europe) LTD

Distribution Centre
Unit 21B Vale Business Park
Llandow, Vale of Glamorgan
CF71 7PF

Telephone: + 44 (0)8445 783 783
Fax: + 44 (0)1446 77 22 47
technical@nav.tv



ALLGIG-HS REN

**VIDEO & NAVIGATION IN MOTION
AV INPUT**

CHRYSLER TOWN & COUNTRY

DODGE CARAVAN

DODGE NITRO

JEEP LIBERTY

JEEP WRANGLER

NAV TV (Europe) LTD

Disclaimer

NAV TV (Europe) Ltd is not liable for any incidental, consequential or indirect damages. In case of erratic behavior of the vehicle's electrical system please disconnect the NAV TV product and contact our technical support Team. NAV TV (Europe) Ltd does not assume liability for any diagnostic fees.

LOCATION & REMOVAL

Example JEEP WRANGLER;


1. Pop the upper and lower covers, the clips are at the rear of the top cover and top of the lower cover.
2. Remove 4 7mm screws holding the radio and A/C trim.
3. Pull the trim just enough to gain access to the radio. There is no need to remove the A/C Controls.
4. Remove 4 7mm screws securing the radio, unplug all plugs and remove the radio.



LOCATION & REMOVAL

Example DODGE CARAVAN;

1. Pry open the screw covers above the radio and remove the 2 screws.
2. Lift up the top cover and remove 2 screws from above the radio.
3. Remove 6 Plastic clips on the lower console, 3 on each side, pull the console back (Clips retain centre of console)
4. Remove 2 screws securing the lower A/C trim panel, pull the trim backwards, unplug A/C controls, traction/hazard switch and clock.
5. Remove 4 screws securing the radio, pull the radio and unplug all the radio connectors.



INSTALLATION

Connect the supplied A/V & CAMERA plug to socket 1 on the radio

Connect the supplied microphone plug to socket 2 on the radio.

Connect the supplied harness to socket 3 on the radio, to the factory harness plug and to the ALLGIG-HS interface.

